

Adaptec® Series 8 RAID: 81605ZQ, 8885Q, 81605Z, 8885, 8805, 8405 12 Gbps PCIe Gen3 Product Family High-Port SAS/SATA RAID Adapters

Maximum Performance

Data center, IT, and general consumer server environments have a broad range of requirements — from basic connectivity to extreme data storage capacities. The effectiveness at which their data is accessed and protected is crucial to their ultimate success. Microsemi Adaptec® 12 Gbps PCle Gen3 Series 8 RAID adapters, coupled with 12 Gbps SSDs, provide maximum read/write bandwidth and IOPS for the most performance-hungry transactional and database applications.

Series 8Q with Adaptec maxCache 3.0

Advancing the performance capabilities of SSD caching to a broader set of application workloads, the Series 8Q with maxCache 3.0 supports read and write back caching. By caching writes to a redundant SSD cache pool (RAID1, RAID1E or RAID5), maxCache 3.0 leverages the performance and latency capabilities of SSD technology for both read and write workloads. The read caching function is also improved with maxCache 3.0, with additional optimizations to the learned-path algorithm. Adaptec maxCache 3.0 SSD Caching software is the only caching solution that supports up to 2 TB of SSD cache.

Integrated Cache Protection

The Series 8 family continues Adaptec's battery-free portfolio. Series 8 adapters can be combined with the AFM-700 flash-based cache protection module (sold separately) to enable instant cache protection. New with Series 8, the Adaptec 81605Z and 81605ZQ models have flash backup embedded on the board, eliminating the need for a daughterboard and further enabling Adaptec customers to do more with less.

Advanced Data Protection and Ease of Use

Advanced data protection and ease of use have not been forgotten in Series 8. Adaptec RAID Code (ARC) delivers maximum reliability with an industry-leading feature set, including all of the RAID levels the industry has come to expect, plus unique features like Flexible Configuration modes for the adapter, Hybrid RAID, and Optimized Disk Utilization (ODU) where no available space is wasted. Adaptec's maxView provides an HTML5 web interface, which can be used in standard desktops and mobile browsers, for all storage configuration and management needs.











Further Resources and Information: www.microsemi.com



Benefits

- Ideal for 12 Gbps performance-hungry server and workstation platforms, without compromising proven Adaptec reliability
- Provides high I/O transaction and high bandwidth processing; solutions that reduce energy consumption and maintenance costs

Key Differentiators

- maxCache 3.0 caching software (Series 8Q only)
- Cache protection via third generation ZMCP;
 AFM-700 (integrated on 81605Z and 81605ZQ, optional for rest of Series 8 products)
- Up to 16 native SAS/SATA ports in a LP/MD2 design
- 12 Gbps and 6 Gbps compatibility with HDD or SSD SAS/SATA devices
- 12 Gbps throughput per SAS port using mini SAS HD connectors
- Microsemi's 12 Gbps RAID-on-Chip (ROC), x8 PCle Gen3 interface with 12 Gbps SAS ports to enable a new generation of performance
- >700K IOPS; 6.6 GB/s sequential reads, 6.2 GB/s sequential writes



Microsemi makes no warranty, representation, or guarantee regarding the information contained herein or the suitability of its products and services for any particular purpose, nor does Microsemi assume any liability whatsoever arising out of the application or use of any product or circuit. The products sold hereunder and any other products sold by Microsemi have been subject to limited testing and should not be used in conjunction with mission-critical equipment or applications. Any performance specifications are believed to be reliable but are not verified, and Buyer must conduct and complete all performance and other testing of the products, alone and together with, or installed in, any end-products. Buyer shall not rely on any data and performance specifications or parameters provided by Microsemi. It is the Buyer's responsibility to independently determine suitability of any products and to test and verify the same. The information provided by Microsemi hereunder is provided "as is, where is" and with all faults, and the entire risk associated with such information is entirely with the Buyer. Microsemi does not grant, explicitly or implicitly, to any party any patent rights, licenses, or any other IP rights, whether with regard to such information is entirely by the provided in this document is proprietary to Microsemi, and Microsemi reserves the right to make any changes to the information in this document or to any products and services at any time without notice.



Adaptec® Series 8 RAID: 81605ZQ, 8885Q, 81605Z, 8885, 8805, 8405 12 Gbps PCle Gen3 Product Family High-Port SAS/SATA RAID Adapters

Key Software Features	 maxCache 3.0 caching software (Series 8Q only) Flexible Configuration: HBA Mode & Auto Volume Mode for automatic deployment Optimized Disk Utilization (multiple arrays per disk) Supports up to 256 SAS or SATA devices using SAS expanders Support for native 4K sector SAS and SATA devices in addition to 512-byte sector devices Hybrid RAID 1 & 10 Quick initialization 	Online Capacity Expansion Copyback Hot Spare Dynamic caching algorithm Native Command Queuing (NCQ) Background initialization Hot-plug drive support RAID Level Migration Hot spares - global, dedicated, and pooled Automatic/manual rebuild of hot spares SES and SAF-TE enclosure management Configurable stripe size S.M.A.R.T. support	 Multiple arrays per disk drive Dynamic sector repair Staggered drive spin-up Bootable array support Support for Tape Devices, Autoloaders MSI-X support for all device drivers for all supported Operating Systems Secure boot support for the uEFI host BIOS USB image available on start.adaptec.com to boot maxView GUI from any USB device for enhanced GUI-based setup and offline maintenance 				
Management Utilities	Adaptec maxView Storage Manager — Web based GUI Management Utility — OS Support: Windows, Linux, Solaris, VMware — Remote configuration, monitoring & notification — Remote firmware updates — SMI-S Support — SMTP	ARCCONF — Command Line Interface — SMI-S support for VMware Adaptec BIOS Configuration Utility (CTRL+A) — Legacy configuration utility — Flashable BIOS support	Adaptec uEFI BIOS Configuration Utility — HII based configuration utility — Flashable BIOS support Adaptec Event Monitor — Lightweight event monitoring and logging tool — Distribute adapter events and notifies user				
Operating Systems	Microsoft Windows, Red Hat Linux, SUSE Linux, Fedora, Debian Linux, Ubuntu Linux, Sun Solaris, FreeBSD, VMware ESXi. The latest drivers are available at start.adaptec.com						
Dimensions	MD2-Low Profile 2.535 "H x 6.6 "L (64 mm x 16	ow Profile 2.535 "H x 6.6 "L (64 mm x 167 mm)					
Operating Temperature	0 °C to 55 °C* (with 200 LFM airflow, without flash); 0 °C to 50 °C* (with 200 LFM airflow, with flash) Note: This adapter contains a powerful RAID processor which requires adequate airflow to operate reliably. Please install this card only into server or PC chassis with at least 200 LFM airflow. *Temperature measured 1 inch from RAID adapter						
Operating Current	0.1 A @ 3.3 VDC; 1.2 A @ 12.0 VDC 8405, 8805, 8885, 8885Q; 1.0 A @ 3.3 VDC; 1.1 A @ 12.0 VDC 81605ZQ, 81605Z						
Regulatory Certification	CE, FCC, UL, C-tick, VCCI, KCC, CNS	_, C-tick, VCCI, KCC, CNS					
Environmental Compliance	RoHS						
MTBF	2 million hours at 40° C						

	SERIES 8Q		SERIES 8			
Adaptec RAID	81605ZQ	8885Q	81605Z	8885	8805	8405
Order Number	2281600-R (Single)	2277100-R (Single)	2287101-R (Single)	2277000-R (Single)	2277500-R (Single)	2277600-R (Single)
RAID Levels	0,1,1E,5,6,10, 50, 60	0,1,1E,5,6,10, 50, 60	0,1,1E,5,6,10, 50, 60	0,1,1E,5,6,10, 50, 60	0,1,1E,5,6,10, 50, 60	0,1,1E,5,6,10, 50, 60
Ports	16 Internal	8 Internal/8 External	16 Internal	8 Internal/8 External	8 Internal	4 Internal
Connectors	4 x SFF-8643	2 x SFF-8643 2 x SFF-8644	4 x SFF-8643	2 x SFF-8643 2 x SFF-8644	2 x SFF-8643	1 x SFF-8643
Bus Interface	8-Lane PCle Gen3	8-Lane PCle Gen3	8-Lane PCIe Gen3	8-Lane PCle Gen3	8-Lane PCle Gen3	8-Lane PCle Gen3
Processor	12 Gbps RoC	12 Gbps RoC	12 Gbps RoC	12 Gbps RoC	12 Gbp/s RoC	12 Gbps RoC
Cache	1024 MB	1024 MB	1024 MB	1024 MB	1024 MB	1024 MB
Cache Protection	Flash backup (embedded) AFM-700 (included)	AFM-700 (included)	Flash backup (embedded) AFM-700 (included)	AFM-700 (optional)	AFM-700 (optional)	AFM-700 (optional)



Warranty

3 years

Microsemi Corporate Headquarters
One Enterprise, Aliso Viejo, CA 92656 USA
Within the USA: +1 (800) 713-4113
Outside the USA: +1 (949) 380-6100
Sales: +1 (949) 380-6136
Fax: +1 (949) 215-4996
email: sales.support@microsemi.com

www.microsemi.com

Microsemi Corporation (Nasdaq: MSCC) offers a comprehensive portfolio of semiconductor and system solutions for communications, defense & security, aerospace and industrial markets. Products include high-performance and radiation-hardened analog mixed-signal integrated circuits, FPGAs, SoCs and ASICs; power management products; timing and synchronization devices and precise time solutions, setting the world's standard for time; voice processing devices; RF solutions; discrete components; Enterprise Storage and Communication solutions, security technologies and scalable anti-tamper products; Ethernet solutions; Power-over-Ethernet ICs and midspans; as well as custom design capabilities and services. Microsemi is headquartered in Aliso Viejo, Calif., and has approximately 4,800 employees globally. Learn more at www.microsemi.com.

©2016 Microsemi Corporation. All rights reserved. Microsemi and the Microsemi logo are registered trademarks of Microsemi Corporation. All other trademarks and service marks are the property of their respective owners.